





3 Warm White LED (3000K)	CRI 80	17W	24W
Lumen Output		2838 lm	4232 lm
LOR	0.80	0.80	0.80
CRI	80	80	80
Total Power		18.8W	25.7W
Power Factor	0.95	0.98	0.98
Running Current	0.09A	0.11A	0.11A
Inrush Current (Std)	21.0A (126us)	32.0A (240us)	32.0A (240us)
Inrush Current (Dim)	13.6A (304us)	29.0A (180us)	29.0A (180us)
Efficacy	120 lm/W	131 lm/W	131 lm/W
Emergency Output (BLF)	454 lm (16%)	465 lm (11%)	465 lm (11%)

4 Neutral White LED (4000K)	CRI 80	17W	24W
Lumen Output		2970 lm	4428 lm
LOR	0.80	0.80	0.80
CRI	80	80	80
Total Power		18.8W	25.7W
Power Factor	0.95	0.98	0.98
Running Current	0.09A	0.11A	0.11A
Inrush Current (Std)	21.0A (126us)	32.0A (240us)	32.0A (240us)
Inrush Current (Dim)	13.6A (304us)	29.0A (180us)	29.0A (180us)
Efficacy	126 lm/W	137 lm/W	137 lm/W
Emergency Output (BLF)	475 lm (16%)	487 lm (11%)	487 lm (11%)



230V 50Hz IP20 508mm 4.6 kg

iMod® Pendant



LED

17W	LED	PN099	LED	17	+	434
24W	LED	PN099	LED	24	+	434

- Translucent design creates a unique and distinctive LED style statement
- Available in a choice of lumen outputs, delivering up to 4428 lumens
- Efficacies up to 137 lm/W
- 72,000 hour life expectancy (L80 B10)
- Comprehensive choice of Gear Types available
- Luminescent Wing offers vivid coloured indirect lighting whilst maintaining white direct illumination
- 2x 2m Suspension Wires with chrome clutches supplied as standard
- Surface version available

Gear types F & G must be operated through a DSI

- A** Integral Driver
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046)


Luminescent Wing Options Shown

331 2x 5m Suspensions (wires only)



iMod® Pendant


Photometrics




434 ULOR: 0.05 DLOR: 0.75

Options

■ Luminescent Wing Options



229 Mars Red



231 Acid Green