

230V
50Hz

IP
20

50mm

3.7 kg



3	Warm White LED (3000K)	CRI 80	8W	12W	17W
	Lumen Output		1096 lm	1546 lm	2103 lm
	LOR		0.78	0.78	0.78
	CRI		80	80	80
	Total Power		9.0W	13.1W	18.2W
	Power Factor		0.90	0.95	0.93
	Running Current		0.04A	0.06A	0.09A
	Inrush Current (Std)		8.0A (80us)	15.0A (204us)	8.0A (80us)
	Inrush Current (Dim)		15.0A (243us)	20.0A (133us)	25.0A (140us)
	Efficacy		94 lm/W	92 lm/W	90 lm/W
	Emergency Output (BLF)		361 lm (33%)	355 lm (23%)	336 lm (16%)

4	Neutral White LED (4000K)	CRI 80	8W	12W	17W
	Lumen Output		1154 lm	1627 lm	2229 lm
	LOR		0.78	0.78	0.78
	CRI		80	80	80
	Total Power		9.0W	13.1W	18.2W
	Power Factor		0.90	0.95	0.93
	Running Current		0.04A	0.06A	0.09A
	Inrush Current (Std)		8.0A (80us)	15.0A (204us)	8.0A (80us)
	Inrush Current (Dim)		15.0A (243us)	20.0A (133us)	25.0A (140us)
	Efficacy		100 lm/W	96 lm/W	95 lm/W
	Emergency Output (BLF)		380 lm (33%)	374 lm (23%)	356 lm (16%)

Vici



LED

8W	LED	PN455	LED	08	+	428
12W	LED	PN455	LED	12	+	428
17W	LED	PN455	LED	17	+	428


- Commercial quality pendant offering life expectancy of 50,000 hours (L80 B10)
- Lumen outputs from 1096 to 2229 lumens
- Efficacies up to 100 lm/W
- Colour stability within 3 MacAdams
- Creatively combines lightly etched borosilicate glass and spun steel housing in a choice of colours
- Wide choice of Gear Types available
- 2m Suspension supplied as standard (optional 5m available)
- Wireless Lighting Control available, see Connected video for full overview

Gear types F & G must be operated through a DSI

- A** Integral Driver/Remote
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency
- L** DALI Bluetooth
- M** DALI Bluetooth + Emergency

- 3** Warm (3000K) **4** Neutral (4000K)
- 1** White (RAL 9010) **2** Urban Graphite (RAL 7046) **3** Black (RAL 9005)
- 330** 5m Suspension (wire only)

Photometrics



428 DLOR: 0.78

Hacel[®]
Fluent in Lighting