





	CRI 80	32W	50W
3 Warm White LED (3000K)			
Lumen Output	4590 lm	6600 lm	
LOR	0.80	0.80	
CRI	80	80	
Total Power	35.3W	54.8W	
Power Factor	0.95	0.95	
Running Current	0.16A	0.25A	
Inrush Current (Std)	24.7A (268us)	25.9A (252us)	
Inrush Current (Dim)	28.0A (195us)	26.0A (264us)	
Efficacy	104 lm/W	96 lm/W	
Emergency Output (BLF)	367 lm (8%)	330 lm (5%)	
4 Neutral White LED (4000K)			
Lumen Output	4890 lm	7080 lm	
LOR	0.80	0.80	
CRI	80	80	
Total Power	35.3W	54.8W	
Power Factor	0.95	0.95	
Running Current	0.16A	0.25A	
Inrush Current (Std)	24.7A (268us)	25.9A (252us)	
Inrush Current (Dim)	28.0A (195us)	26.0A (264us)	
Efficacy	110 lm/W	103 lm/W	
Emergency Output (BLF)	391 lm (8%)	354 lm (5%)	



230V
50Hz

IP
20

470mm Ø

3.7 kg

Solos[®] Recessed



LED

32W	LED	ID161	LED	32	+	354
50W	LED	ID161	LED	50	+	354

Control Devices



Microwave/PIR Controller	CD295	X	PIR000
Microwave/PIR Programmer	CD296	X	PIR000

Gear type F & G must be operated through a DSI

- A** Integral Driver/Remote
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim (ID161 only)
- K** Switch Dim + Emergency (ID161 only)
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency
- L** DALI Bluetooth (ID161 only)
- M** DALI Bluetooth + Emergency (ID161 only)

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

Luminescent Halo - Examples Shown on page 2

- High performance LED
- Available in a choice of lumen outputs, delivering up to 7080 lumens
- Efficacies up to 110 lm/W
- Colour stability within 3 MacAdams
- 100,000 hour life expectancy (L80 B10)
- Microwave Control is discreetly concealed behind diffuser
- Slim recessing depth of only 69mm
- Centre feature and housing available in White (shown), Black or Urban Graphite
- The microwave sensor defaults can be modified via dip switches for non-dimmable versions and with the use of the Microwave/PIR controller for dimmable versions (contact Technical for advice if required)
- TP(b) rated as standard
- Complementary, Surface and Pendant versions are available
- Wireless Lighting Control available, see Connected video for full overview
- Dip switch settings can be found on Installation document - default setting is 5mins



Solos[®] Recessed

Options

■ Luminescent Halo Options




469 Neptune Blue

470 Mars Red

472 Acid Green

Photometrics



354 DLOR: 0.80