



3	Warm White LED (3000K)	CRI 80 43W
	Lumen Output	5432 lm
	LOR	0.81
	CRI	80
	Total Power	49.9W
	Power Factor	0.95
	Running Current	0.23A
	Inrush Current (Std)	45.0A
	Inrush Current (Dim)	43.0A
	Efficacy	88 lm/W
	Emergency Output (BLF)	N/a
4	Neutral White LED (4000K)	CRI 80 43W
	Lumen Output	5460 lm
	LOR	0.81
	CRI	80
	Total Power	49.9W
	Power Factor	0.95
	Running Current	0.23A
	Inrush Current (Std)	45.0A
	Inrush Current (Dim)	43.0A
	Efficacy	88 lm/W
	Emergency Output (BLF)	N/a

- Elegant LED pendant with Chrome feature
- Can be mechanically linked to create an array of imaginative configurations
- Lumen outputs from 5432 to 5460 lumens
- Efficacies of up to 88 lm/W, CRI 80
- Life expectancy of 50,000hrs (L80 B10)
- Colour stability within 3 MacAdams
- Colour options apply to Driver Housing
- Complementary Wall Light available
- Wireless Lighting Control available, see Connected video for full overview

Explora® Star Pendant

Solo



LED CRI 80

43W LED Micro PN1214 — LED — 43 — + 564


Link



LED CRI 80

43W LED Micro PN1225 — LED — 43 — + 564

Photometrics



564 ULOR: 0.40 DLOR: 0.41

- A** Integral Driver/Remote
- J** Switch Dim
- S** DALI Dim
- L** DALI Bluetooth

— **3** Warm (3000K) — **4** Neutral (4000K)

— **1** White (RAL 9010) — **2** Urban Graphite (RAL 7046) — **3** Black (RAL 9005) *Colour options apply to Driver Housing*

— **264** 3x 5m Suspensions (wires only)



Explora® Star Pendant

