

3	Warm White LED (3000K)	CRI 80			CRI 90		
		12W	24W	42W	12W	24W	42W
	Lumen Output	1824 lm	3796 lm	6190 lm	1548 lm	3266 lm	5136 lm
	LOR	0.81	0.81	0.81	0.81	0.81	0.81
	CRI	80	80	80	90	90	90
	Total Power	14.0W	26.4W	46.0W	14.0W	26.4W	46.0W
	Power Factor	0.98	0.98	0.98	0.98	0.98	0.98
	Running Current	0.06A	0.11A	0.20A	0.06A	0.11A	0.20A
	Inrush Current (Std)	20.0A (200us)	20.0A (200us)	40.0A (200us)	20.0A (200us)	20.0A (200us)	40.0A (200us)
	Inrush Current (Dim)	20.0A (200us)	20.0A (200us)	30.0A (200us)	20.0A (200us)	20.0A (200us)	30.0A (200us)
	Efficacy	105 lm/W	116 lm/W	108 lm/W	89 lm/W	100 lm/W	90 lm/W
	Emergency Output (BLF)	N/A	N/A	N/A	N/A	N/A	N/A

4	Neutral White LED (4000K)	CRI 80			CRI 90		
		12W	24W	42W	12W	24W	42W
	Lumen Output	1924 lm	4008 lm	6578 lm	1548 lm	3654 lm	5342 lm
	LOR	0.81	0.81	0.81	0.81	0.81	0.81
	CRI	80	80	80	90	90	90
	Total Power	14.0W	26.4W	46.0W	14.0W	26.4W	46.0W
	Power Factor	0.98	0.98	0.98	0.98	0.98	0.98
	Running Current	0.06A	0.11A	0.20A	0.06A	0.11A	0.20A
	Inrush Current (Std)	20.0A (200us)	20.0A (200us)	40.0A (200us)	20.0A (200us)	20.0A (200us)	40.0A (200us)
	Inrush Current (Dim)	20.0A (200us)	20.0A (200us)	30.0A (200us)	20.0A (200us)	20.0A (200us)	30.0A (200us)
	Efficacy	111 lm/W	122 lm/W	115 lm/W	89 lm/W	112 lm/W	94 lm/W
	Emergency Output (BLF)	N/A	N/A	N/A	N/A	N/A	N/A

Azuma® Maxi Duet

LED CRI 80		LED CRI 90	
12W	LED WL481	LED WL482	12
24W	LED WL481	LED WL482	24
42W	LED WL481	LED WL482	42

- Class leading, high quality LED Wall Light with a clean design and finned detailing
- Available in a choice of lumen outputs, delivering up to 6578 lumens
- Efficacies up to 122 lm/W
- Single point Zhaga Book 3 LED
- Medium beam reflector as standard
- Life expectancy in excess of 60,000 hours (L80 B10)
- Colour stability within 3 MacAdams
- Complementary Power Spots available
- Wireless Lighting Control available, see Connected video for full overview

Gear type F must be operated through a DSI

- A Integral Driver/Remote
- J Switch Dim
- S DALI Dim
- L DALI Bluetooth

- 3 Warm (3000K) 4 Neutral (4000K)
- 1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

Reflector	CRI 80	CRI 90
480 2x Narrow Beam	455	456
481 2x Wide Beam	457	458

Baffle Option - Examples Shown on page 2



Azuma® Maxi Duet


Options

- **Baffle** Option




541 2x Anti Glare Baffle


Photometrics



453-454 DLOR: 0.81



455-456 DLOR: 0.83



457-458 DLOR: 0.86