

3	Warm White LED (3000K)	CRI 80			CRI 90		
		6W	12W	21W	6W	12W	21W
	Lumen Output	912 lm	1898 lm	3095 lm	774 lm	1633 lm	2568 lm
	LOR	0.81	0.81	0.81	0.81	0.81	0.81
	CRI	80	80	80	90	90	90
	Total Power	7.0W	13.7W	22.7W	7.0W	13.7W	22.7W
	Power Factor	0.98	0.98	0.98	0.98	0.98	0.98
	Running Current	0.03A	0.06A	0.10A	0.03A	0.06A	0.10A
	Inrush Current (Std)	20.0A (200us)	20.0A (200us)	20.0A (200us)	20.0A (200us)	20.0A (200us)	20.0A (200us)
	Inrush Current (Dim)	5.0A (100us)	20.0A (200us)	20.0A (200us)	5.0A (100us)	20.0A (200us)	20.0A (200us)
	Efficacy	105 lm/W	112 lm/W	110 lm/W	89 lm/W	96 lm/W	91 lm/W
	Emergency Output (BLF)	N/A	N/A	N/A	N/A	N/A	N/A

4	Neutral White LED (4000K)	CRI 80			CRI 90		
		6W	12W	21W	6W	12W	21W
	Lumen Output	962 lm	2004 lm	3289 lm	817 lm	1827 lm	2671 lm
	LOR	0.81	0.81	0.81	0.81	0.81	0.81
	CRI	80	80	80	90	90	90
	Total Power	7.0W	13.7W	22.7W	7.0W	13.7W	22.7W
	Power Factor	0.98	0.98	0.98	0.98	0.98	0.98
	Running Current	0.03A	0.06A	0.10A	0.03A	0.06A	0.10A
	Inrush Current (Std)	20.0A (200us)	20.0A (200us)	20.0A (200us)	20.0A (200us)	20.0A (200us)	20.0A (200us)
	Inrush Current (Dim)	5.0A (100us)	20.0A (200us)	20.0A (200us)	5.0A (100us)	20.0A (200us)	20.0A (200us)
	Efficacy	111 lm/W	118 lm/W	117 lm/W	94 lm/W	108 lm/W	114 lm/W
	Emergency Output (BLF)	N/A	N/A	N/A	N/A	N/A	N/A

Azuma® Maxi Solo

LED CRI 80

6W	LED	WL479	LED	06	+	453
12W	LED	WL479	LED	12	+	453
21W	LED	WL479	LED	21	+	453

LED CRI 90

6W	LED	WL480	LED	06	+	454
12W	LED	WL480	LED	12	+	454
21W	LED	WL480	LED	21	+	454

Gear type F must be operated through a DSI

- A** Integral Driver/Remote
- J** Switch Dim
- S** DALI Dim
- L** DALI Bluetooth

3 Warm (3000K) **4** Neutral (4000K)

1 White (RAL 9010) **2** Urban Graphite (RAL 7046) **3** Black (RAL 9005)

Reflector		CRI 80	CRI 90
384	Narrow Beam	455	456
385	Wide Beam	457	458

Baffle Option - Examples Shown on page 2

- Class leading, high quality LED Wall Light with a clean design and finned detailing
- Available in a choice of lumen outputs, delivering up to 3289 lumens
- Efficacies up to 118 lm/W
- Single point Zhaga Book 3 LED
- Medium beam reflector as standard
- Life expectancy in excess of 60,000 hours (L80 B10)
- Colour stability within 3 MacAdams
- Complementary Power Spots available
- Wireless Lighting Control available, see Connected video for full overview



Azuma® Maxi Solo


Options

- **Baffle** Option




540 Anti Glare Baffle


Photometrics



453-454 DLOR: 0.81



455-456 DLOR: 0.83



457-458 DLOR: 0.86