




3	Daylight White LED (6500K)	CRI 70 2W
	Lumen Output	206 lm
	LOR	1.0
	CRI	80
	Total Power	2.5W
	Power Factor	0.63
	Running Current	0.02 A
	Inrush Current	10A (120us)
	Efficacy	82 lm/W
	Emergency Output (BLF)	206 lm (100%)



230V
50Hz

IP 20

43mm Ø

0.3 kg

Maximum ceiling thickness 25mm

Emy




LED

2W LED ID1207 LED 002 1 548/549/550

Lenses included:



Anti-Panic




Escape Route




Spot

- Stand alone, three hour rated, non-maintained Emergency LED
- Three lenses included:
 - Anti-Panic: For general emergency lighting applications
 - Escape Route: For corridor and escape route lighting applications
 - Spot: For highlighting emergency equipment
- Daylight colour temperature (6500K)
- Efficacies up to 82 lm/W
- Output 206 lumens in emergency mode
- Life expectancy in excess of 50,000 hours (L90 B50)
- Colour stability within 3 MacAdams
- Lithium Iron Phosphate battery


Photometrics



548 DLOR: 1.00



549 DLOR: 1.00



550 DLOR: 1.00

E Emergency
C DALI Emergency
Z Self Test Emergency

1 White (RAL 9010) **3** Black (RAL 9005)

Tel: (0191) 280 9911 Email: technical@hacel.co.uk Web: www.hacel.co.uk

08/2023 - V3

Hacel
Fluent in Lighting