

|                        | CRI 80 | Warm White LED (3000K) |               |               |               |
|------------------------|--------|------------------------|---------------|---------------|---------------|
|                        |        | 8W                     | 11W           | 16W           | 30W           |
| Lumen Output           |        | 1488 lm                | 2071 lm       | 2929 lm       | 5123 lm       |
| LOR                    |        | 0.90                   | 0.90          | 0.90          | 0.90          |
| CRI                    |        | 80                     | 80            | 80            | 80            |
| Total Power            |        | 9.1W                   | 12.8W         | 18W           | 33.4W         |
| Power Factor           |        | 0.95                   | 0.95          | 0.95          | 0.95          |
| Running Current        |        | 0.04A                  | 0.05A         | 0.07A         | 0.12A         |
| Inrush Current (Std)   |        | 15.0A (204us)          | 15.0A (204us) | 24.7A (268us) | 24.7A (268us) |
| Inrush Current (Dim)   |        | 18.0A (140us)          | 18.0A (140us) | 28.0A (195us) | 28.0A (195us) |
| Efficacy               |        | 147 lm/W               | 145 lm/W      | 146 lm/W      | 138 lm/W      |
| Emergency Output (BLF) |        | 386 lm (26%)           | 393 lm (19%)  | 380 lm (13%)  | 358 lm (7%)   |

|                        | CRI 80 | Neutral White LED (4000K) |               |               |               |
|------------------------|--------|---------------------------|---------------|---------------|---------------|
|                        |        | 8W                        | 11W           | 16W           | 30W           |
| Lumen Output           |        | 1551 lm                   | 2159 lm       | 3054 lm       | 5342 lm       |
| LOR                    |        | 0.90                      | 0.90          | 0.90          | 0.90          |
| CRI                    |        | 80                        | 80            | 80            | 80            |
| Total Power            |        | 9.1W                      | 12.8W         | 18W           | 33.4W         |
| Power Factor           |        | 0.95                      | 0.95          | 0.95          | 0.95          |
| Running Current        |        | 0.04A                     | 0.05A         | 0.07A         | 0.12A         |
| Inrush Current (Std)   |        | 15.0A (204us)             | 15.0A (204us) | 24.7A (268us) | 24.7A (268us) |
| Inrush Current (Dim)   |        | 18.0A (140us)             | 18.0A (140us) | 28.0A (195us) | 28.0A (195us) |
| Efficacy               |        | 153 lm/W                  | 151 lm/W      | 152 lm/W      | 143 lm/W      |
| Emergency Output (BLF) |        | 403 lm (26%)              | 410 lm (19%)  | 397 lm (13%)  | 373 lm (7%)   |

## Solex® Pendant



### LED

|     |     |        |     |    |   |     |
|-----|-----|--------|-----|----|---|-----|
| 8W  | LED | PN1298 | LED | 08 | + | 642 |
| 11W | LED | PN1298 | LED | 11 | + | 642 |
| 16W | LED | PN1298 | LED | 16 | + | 642 |
| 30W | LED | PN1298 | LED | 30 | + | 642 |

Gear types F & G must be operated through a DSI

- A** Integral Driver/Remote
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency
- L** DALI Bluetooth
- M** DALI Bluetooth + Emergency

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

### Reflector

641 Narrow Beam

Polycarbonate Options - Examples Shown on page 2

- Efficacies up to 153 lm/W
- Lumen outputs from 1488 to 5342 lumens
- Life expectancy in excess of 50,000 hours (L90 B10)
- Colour stability within 3 MacAdams
- Positive clamp fixings for ease of installation
- Range of options for customisation available
- Complementary Solex® Downlighter and Surface versions available
- Wireless Lighting Control available, see Connected video for full overview



## Solex® Pendant Options

### ■ Polycarbonate Options



581 Flush Clear




582 Flush Etched




585 Cylo Etched Ice

### Photometrics



641 DLOR: 0.90



642 DLOR: 0.90