




3 Warm White LED (3000K)	CRI 80	15W	32W	50W
Lumen Output		2795 lm	5405 lm	8241 lm
LOR		0.70	0.70	0.70
CRI		80	80	80
Total Power		17.2W	34.1W	54.3W
Power Factor		0.87	0.96	0.95
Running Current		0.7A	0.14A	0.22A
Inrush Current (Std)		2.9A (61us)	25.0A (150us)	25.9A (252us)
Inrush Current (Dim)		25.0A (140us)	28.0A (165us)	26.0A (264us)
Efficacy		113 lm/W	110 lm/W	106 lm/W
Emergency Output (BLF)		395 lm (14%)	387 lm (7%)	412 lm (5%)

4 Neutral White LED (4000K)	CRI 80	15W	32W	50W
Lumen Output		2969 lm	5743 lm	8756 lm
LOR		0.70	0.70	0.70
CRI		80	80	80
Total Power		17.2W	34.1W	54.3W
Power Factor		0.87	0.96	0.95
Running Current		0.7A	0.14A	0.22A
Inrush Current (Std)		2.9A (61us)	25.0A (150us)	25.9A (252us)
Inrush Current (Dim)		25.0A (140us)	28.0A (165us)	26.0A (264us)
Efficacy		120 lm/W	117 lm/W	112 lm/W
Emergency Output (BLF)		417 lm (14%)	411 lm (7%)	438 lm (5%)



Solos® Pendant

LED	15W	32W	50W
LED	PN287	PN287	PN287
LED	15	32	50
	+	+	+
	737	737	737

Gear types F & G must be operated through a DSI


- A** Integral Driver/Remote
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency
- L** DALI Bluetooth
- M** DALI Bluetooth + Emergency

- 3** Warm (3000K) **4** Neutral (4000K)
- 1** White (RAL 9010) **2** Urban Graphite (RAL 7046) **3** Black (RAL 9005)

Luminescent Halo Options - Examples Shown on page 2


353 3x 5m Suspensions (wires only)

- Slim circular contemporary luminaire
- High performance LED offering 65,000 hour life expectancy (L80 B10)
- Lumen outputs from 2795 to 8756 lumens
- Efficacies up to 120 lm/W
- Colour stability within 3 MacAdams
- 2m suspension supplied as standard (Optional 5m)
- Centre feature and housing available in White, Black and Graphite (shown)
- Complementary Downlight, Surface and Wall Light versions are available
- Wireless Lighting Control available, see Connected video for full overview




Solos[®] Pendant


■ Luminescent Halo Options



469 Neptune Blue




470 Mars Red



472 Acid Green

Photometrics



737 DLOR: 0.70