




3 Warm White LED (3000K)	CRI 80	15W	32W	50W
Lumen Output		2795 lm	5405 lm	8241 lm
LOR		0.60	0.60	0.60
CRI		80	80	80
Total Power		17.2W	34.1W	54.3W
Power Factor		0.9	0.96	0.95
Running Current		0.09A	0.16A	0.22A
Inrush Current (Std)		2.9A (61us)	25.0A (150us)	25.9A (252us)
Inrush Current Dim)		25A (140us)	28.0A (165us)	26.0A (264us)
Efficacy		97 lm/W	95 lm/W	91 lm/W
Emergency Output (BLF)		395 (14%)	387 lm (7%)	412 lm (5%)

4 Neutral White LED (4000K)	CRI 80	15W	32W	50W
Lumen Output		2969 lm	5743 lm	8756 lm
LOR		0.60	0.60	0.60
CRI		80	80	80
Total Power		17.2W	34.1W	54.3W
Power Factor		0.9	0.96	0.95
Running Current		0.09A	0.16A	0.22A
Inrush Current (Std)		2.9A (61us)	25.0A (150us)	25.9A (252us)
Inrush Current Dim)		25A (140us)	28.0A (165us)	26.0A (264us)
Efficacy		103 lm/W	101 lm/W	96 lm/W
Emergency Output (BLF)		417 (14%)	411 lm (7%)	438 lm (5%)



Solos[®] Recessed



LED

15W	LED	ID161	LED	15	+	736
32W	LED	ID161	LED	32	+	736
50W	LED	ID161	LED	50	+	736

LED & MW

15W	LED	ID169	LED	15	+	736
32W	LED	ID169	LED	32	+	736
50W	LED	ID169	LED	50	+	736

MW versions not suitable for use with Gear Types J and K.

Control Devices



Microwave/PIR Controller	CD295	X	PIR000
Microwave/PIR Programmer	CD296	X	PIR000

230V
50Hz

IP
20

470mm Ø

3.7 kg

- High performance LED Circular light offering 65,000 hour life expectancy (L80 B10)
- Lumen outputs from 2795 to 8756 lumens
- Efficacies up to 103 lm/W
- Colour stability within 3 MacAdams
- Microwave Control is discreetly concealed behind diffuser
- Slim recessing depth of only 69mm
- Centre feature and housing available in White (shown), Black or Urban Graphite
- TP(b) rated as standard
- Complementary, Surface and Pendant versions are available
- Wireless Lighting Control available, see Connected video for full overview

- A** Integral Driver/Remote
- E** Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency
- L** DALI Bluetooth
- M** DALI Bluetooth + Emergency

3 Warm (3000K) **4** Neutral (4000K)

1 White (RAL 9010) **2** Urban Graphite (RAL 7046) **3** Black (RAL 9005)

Luminescent Halo - Examples Shown on page 2



Solos[®] Recessed

Options

■ Luminescent Halo Options



469 Neptune Blue




470 Mars Red



472 Acid Green

Photometrics



736 DLOR: 0.61