

230V 50Hz **IP** 20  $\phi$  50mm 3.7 kg

3 Warm White LED (3000K)	CRI 80	8W	12W	17W
Lumen Output		1096 lm	1546 lm	2103 lm
LOR		0.78	0.78	0.78
CRI		80	80	80
Total Power		9.0W	13.1W	18.2W
Power Factor		0.90	0.95	0.93
Running Current		0.04A	0.06A	0.09A
Inrush Current (Std)		8.0A (80us)	15.0A (204us)	8.0A (80us)
Inrush Current (Dim)		15.0A (243us)	20.0A (133us)	25.0A (140us)
Efficacy		94 lm/W	92 lm/W	90 lm/W
Emergency Output (BLF)		361 lm (33%)	355 lm (23%)	336 lm (16%)

4 Neutral White LED (4000K)	CRI 80	8W	12W	17W
Lumen Output		1154 lm	1627 lm	2229 lm
LOR		0.78	0.78	0.78
CRI		80	80	80
Total Power		9.0W	13.1W	18.2W
Power Factor		0.90	0.95	0.93
Running Current		0.04A	0.06A	0.09A
Inrush Current (Std)		8.0A (80us)	15.0A (204us)	8.0A (80us)
Inrush Current (Dim)		15.0A (243us)	20.0A (133us)	25.0A (140us)
Efficacy		100 lm/W	96 lm/W	95 lm/W
Emergency Output (BLF)		380 lm (33%)	374 lm (23%)	356 lm (16%)

## Vici




### LED

8W	LED	PN455	LED	08	+	428
12W	LED	PN455	LED	12	+	428
17W	LED	PN455	LED	17	+	428

- Commercial quality pendant offering life expectancy of 50,000 hours (L80 B10)
- Lumen outputs from 1096 to 2229 lumens
- Efficacies up to 100 lm/W
- Colour stability within 3 MacAdams
- Creatively combines lightly etched borosilicate glass and spun steel housing in a choice of colours
- Wide choice of Gear Types available
- 2m Suspension supplied as standard (optional 5m available)
- Wireless Lighting Control available
- Digital Dim and Digital Dim + Emergency options available

### Photometrics



428 DLOR: 0.78

- A** Integral Driver/Remote
- E** Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency
- L** DALI Bluetooth
- M** DALI Bluetooth + Emergency

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

330 5m Suspension (wire only)

Tel: (0191) 280 9911 Email: [technical@hacel.co.uk](mailto:technical@hacel.co.uk) Web: [www.hacel.co.uk](http://www.hacel.co.uk)

V4 - 05/2026

\* All values provided in this document are subject to International standards and electronic components from leading suppliers which are subject to +/- 10% tolerance and apply at an ambient temperature of 25°C. Hacel Lighting look to constantly improve it's product and reserve the right to change specifications without prior notification.